

THE

OHAUS ES SERIES

Low profile bench scales



Utility and economy come together in the ES Series of all-purpose bench scales. The low profile design of the ES Series scales makes them perfect for shipping, receiving, and general bench applications. Easy, two-button operation and a large display guarantee accurate and unmistakable results. The unique 3-way mounting bracket allows you to mount the indicator to the scale base, above the scale platform, or on any vertical surface. For simple weighing at a favorable cost, the ES Series is the scale to choose.

- 6 Models to choose from - 6 kg to 200 kg (13.2 lb to 440 lb)
- Features kg, lb, oz and lb:oz units
- Plug and Weigh - Ready to use
- AC and battery power
- 1 year warranty



Ohaus ES Series

Low Profile Bench Scales



ES Series

Model	ES6R	ES30R	ES50R	ES50L	ES100L	ES200L	
Capacity x Readability	(kg)	6 x 0.002	30 x 0.01	50 x 0.02	50 x 0.02	100 x 0.05	200 x 0.1
	(lb)	13 x 0.005	66 x 0.05	110 x 0.05	110 x 0.05	220 x 0.1	440 x 0.2
	(oz)	211 x 0.1	1056 x 0.5	1760 x 1.0	1760 x 1.0	3520 x 2.0	7040 x 5.0
	(lb:oz)	13 lb 3 oz x 1 oz	66 lb x 1 oz	110 lb x 1 oz	110 lb x 1 oz	220 lb x 2 oz	n/a
Weighing Units	kg, lb, oz, lb:oz					kg, lb, oz	
Base Size (in/cm)	12.2 x 10.8 x 1.5 / 31 x 27 x 4			20.5 x 15.7 x 3 / 52 x 40 x 7.5			
Mounting Bracket (in/cm)	4 / 10			4 / 10			
Platform Construction	Stainless steel / baked enamel frame			Stainless steel / powder coated frame			
Scale Weight (lb/kg)	6.6 / 3			33 / 15			
Shipping Weight (lb/kg)	8.8 / 4			38 / 17			
Shipping Dimensions (in/cm)	13 x 15 x 5.5 / 32 x 37 x 14			19 x 24 x 9 / 48 x 60 x 23			
Span Calibration	100 %			50 %			
Display (in/cm)	LCD 1 inch / 2.54 cm (digit height)						
Keyboard	Two function membrane switches						
Power	9VDC / AC adapter (included) or six AA batteries (not included)						
Typical battery life	120 hours / 30 hours of continuous use						
Stabilization Time (typical)	Within 3 seconds						
Storage Temperature	-10° C to 70° C						
Operating Temperature	-10° C to 40° C						

Meets Requirements of Approval Agencies: UL, FCC, CSA, CE Safety EN60950, Emissions EN55022, Immunity EN50082-1

Standard Features

Easy two-button operation, Stability indicator, Auto-zero tracking, Battery saving auto-off timer, (after 5 minutes of inactivity), 3-way mounting bracket (mounts indicator to base, above base, or to wall), AC power adapter, large platforms feature leveling feet.

Industry Leading Warranty

All Ohaus ES bench scales are protected by a 12 month warranty on labor and parts. Our rugged construction and stringent quality control have been the hallmarks of Ohaus scales and balances since 1907.

Simple To Order

Contact your dealer for product availability.

Ohaus Corporation

* 29 Hanover Road
Florham Park, NJ 07932 USA
Tel: 973-377-9000
Fax: 973-593-0359

With offices with offices throughout Europe, Asia, and Latin America

* ISO 9001

Registered Quality Management System

Internet Address: www.ohaus.com

LUS03-00 ©Copyright Ohaus Corporation

